



IT'S JUST THAT SIMPLE™



NO SPECIAL EQUIPMENT NEEDED

Using any industrial cart or dolly, move the Cyclone Barrel Pack to your desired pulling location. Always secure the Cyclone Barrel Pack with a chain or strap when using a cart or dolly.



NO EXTRA TOOLS NEEDED

Remove the Cyclone Barrel Pack lid, detach wire from its secured position and attach wire to your pull rope.



PROPER HANDLING

Position the Cyclone Barrel Pack upright. Do not stack, tip or roll.



EFFORTLESS PULLING

No tangles, no tools, just pull! See it for yourself by scanning the QR code to the right.



Advantages of the Cyclone Barrel Pack



- 120V/208Y and 277V/480Y color-coding
- Portable and easy to set up
- Barrel serves as an instant payoff system
- Eliminates the need for multiple reels
- Lowers the amount of wire scrap produced
- Less waste created by barrel pack vs. reel
- Money and time savings on job site or OEM shop
- Less space on a truck than traditional reels
- Longer continual runs
- Available in 14 AWG through 10 AWG up to 7 conductors
- Easily customized to any specific job
- Available in 55 and 75 gallon drums
- THHN-2/THWN-2, XHHW-2, USE-2 and MTW

**THHN/THWN-2 COPPER CONDUCTOR
FOOTAGE CHART**

Wire Type	Length (ft)	Total Footage (ft)
14/2 STR THHN/THWN-2	10,500'	21,000'
14/3 STR THHN/THWN-2	9,000'	27,000'
14/4 STR THHN/THWN-2	7,000'	28,000'
14/5 STR THHN/THWN-2	7,000'	35,000'
14/6 STR THHN/THWN-2	5,000'	30,000'
14/7 STR THHN/THWN-2	5,000'	35,000'
12/2 STR THHN/THWN-2	8,000'	16,000'
12/3 STR THHN/THWN-2	6,750'	20,250'
12/4 STR THHN/THWN-2	5,000'	20,000'
12/5 STR THHN/THWN-2	5,000'	25,000'
12/6 STR THHN/THWN-2	3,000'	18,000'
12/7 STR THHN/THWN-2	3,000'	21,000'
10/2 STR THHN/THWN-2	5,000'	10,000'
10/3 STR THHN/THWN-2	4,250'	12,750'
10/4 STR THHN/THWN-2	3,000'	12,000'
10/5 STR THHN/THWN-2	3,000'	15,000'
10/6 STR THHN/THWN-2	2,500'	15,000'
10/7 STR THHN/THWN-2	2,500'	17,500'

For other wire types such as XHHW-2 & USE-2, and aluminum, please contact your local Encore Wire sales representative.

